

**SAFETY DATA SHEET**

REVISION DATE: 05-21-2015

SUPERSEDES: 03-19-2015

**SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER****PRODUCT INFORMATION**

PRODUCT: FOSTER 90-66 PART B  
PRODUCT DESCRIPTION: Sealer/coating  
INTENDED USE: Adhesive  
PRODUCT IDENTIFIER: 802432PM

**COMPANY INFORMATION**

H.B. Fuller Company  
1200 Willow Lake Boulevard  
Vadnais Heights, MN 55110  
Phone: 888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 2: HAZARDS IDENTIFICATION****GHS Hazard Symbols:****GHS Signal Word:**

Danger

**GHS Classification:**

Germ Cell Mutagenicity Category 1B; Carcinogenicity Category 1B; Skin Corrosion/Irritation Category 2; Reproductive Toxicity Category 2; Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2; Hazardous to the aquatic environment - Acute Category 2; Hazardous to the aquatic environment - Chronic Category 2; Flammable Liquid Category 3

**GHS Hazard Phrases:**

Flammable liquid and vapour.; Causes skin irritation.; May cause genetic defects.; May cause cancer.; Suspected of damaging fertility or the unborn child.; May cause damage to organs through prolonged or repeated exposure.; Toxic to aquatic life.; Toxic to aquatic life with long lasting effects.

**GHS Precautions:****Safety Precautions:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

**First Aid Measures:**

IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to

Print Date: 06-01-2015

FOSTER 90-66 PART B  
802432PM**SAFETY DATA SHEET**

**Storage:** extinguish. Collect spillage. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

| Chemical Name                 | CAS #      | PERCENT | Classification  | Note         |
|-------------------------------|------------|---------|---|--------------|
| Carbon black                  | 1333-86-4  | 30 - 50 | Carc. 2; H351   | *(see below) |
| Aromatic petroleum distillate | 64742-95-6 | 10 - 30 | Asp. Tox. 1; H304<br>Carc. 1B; H350<br>Muta. 1B; H340   |              |
| Toluene                       | 108-88-3   | 5 - 10  | Asp. Tox. 1; H304<br>Acute Tox. 4; H302<br>Flam. Liq. 2; H225<br>Repr. 2; H361<br>Skin Irrit. 2; H315<br>STOT RE 2; H373<br>STOT SE 3; H336 |              |
| Manganese compounds           | 1313-13-9  | 5 - 10  | Acute Tox. 4; H332<br>Acute Tox. 4; H302  | *(see below) |
| Trimethylbenzene, 1,2,4-      | 95-63-6    | 5 - 10  | Aquatic Chronic 2; H411<br>Acute Tox. 4; H332<br>Eye Irrit. 2; H319<br>Flam. Liq. 3; H226<br>Skin Irrit. 2; H315<br>STOT SE 3; H335         |              |
| Hydrogenated terphenyls       | 61788-32-7 | 1 - 5   | Aquatic Acute 1; H400<br>Aquatic Chronic 4; H413<br>Acute Tox. 4; H332  |              |
| Polybutene                    | 9003-29-6  | 1 - 5   | Aquatic Chronic 4; H413   |              |
| Terphenyls                    | 26140-60-3 | 1 - 5   | Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410  |              |

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

**SECTION 4: FIRST AID MEASURES**

**IF IN EYES:** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

**IF ON SKIN:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

**IF INHALED:** Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

**IF SWALLOWED:** Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

**SAFETY DATA SHEET****SECTION 5: FIRE FIGHTING MEASURES**

|                                     |   |
|-------------------------------------|---|
| EXTINGUISHING MEDIA:                | Use water spray, foam, dry chemical or carbon dioxide.  |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: | Vapors are heavier than air and can travel to a source of ignition and flash back.                                      |
| SPECIAL FIRE FIGHTING INSTRUCTIONS: | Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. |
| HAZARDOUS COMBUSTION PRODUCTS:      | Carbon dioxide, Carbon monoxide Manganese dioxide   |

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

|                       |  |
|-----------------------|--|
| SPECIAL PROTECTION:   | Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation. |
| METHODS FOR CLEAN-UP: | Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.<br>Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.  |

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 7: HANDLING AND STORAGE**

|           |   |
|-----------|---|
| Handling: | Avoid contacting and avoid breathing the material. Use only in a well ventilated area.<br>Keep away from heat, sparks and flame.<br>Wash thoroughly after handling.<br>Keep container closed.<br>Emptied container retains vapor and product residue.<br>Observe all labeled precautions until container is cleaned.<br>Drums of this material should be grounded when pouring.<br><b>DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.</b> |
|-----------|---|

Storage: Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and other sources of ignition. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****EXPOSURE LIMITS:**

| Chemical Name           | Note          | ACGIH EXPOSURE LIMITS                        | OSHA PEL                       |
|-------------------------|---------------|--|--------------------------------|
| Carbon black            | * (see below) | 3 mg/m <sup>3</sup> TWA (inhalable fraction) | 3.5 mg/m <sup>3</sup> TWA      |
| Toluene                 |               | 20 ppm TWA                                   | 200 ppm TWA<br>300 ppm Ceiling |
| Hydrogenated terphenyls |               | 0.5 ppm TWA (non-irradiated)                 | Not established                |

Print Date: 06-01-2015

FOSTER 90-66 PART B  
802432PM**SAFETY DATA SHEET**

|            |  |   |   |
|------------|--|---|---|
| Terphenyls |  | No data available.<br>5 mg/m <sup>3</sup> Ceiling | 1 ppm Ceiling; 9 mg/m <sup>3</sup> Ceiling  |
| Xylene     |  | 100 ppm TWA<br>150 ppm STEL                       | 100 ppm TWA; 435 mg/m <sup>3</sup> TWA  |
| Cumene     |  | 50 ppm TWA  | 50 ppm TWA; 245 mg/m <sup>3</sup> TWA<br>Skin absorption may potentially contribute to the overall exposure to this material. |

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

**ENGINEERING CONTROL METHODS:**

|                                |  |
|--------------------------------|--|
| <b>VENTILATION:</b>            | Use local exhaust ventilation or other engineering controls to minimize exposures.   |
| <b>EYE PROTECTION:</b>         | Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.   |
| <b>SKIN PROTECTION:</b>        | Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.  |
| <b>GLOVES:</b>                 | Nitrile  |
| <b>RESPIRATORY PROTECTION:</b> | Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with organic vapor cartridge. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134). |

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

|  |                              |
|--|------------------------------|
| <b>PHYSICAL STATE:</b>                   | Liquid                       |
| <b>COLOR:</b>                            | Black                        |
| <b>ODOR:</b>                             | Solvent                      |
| <b>ODOR THRESHOLD:</b>                   | Not established              |
| <b>pH:</b>                               | Not established              |
| <b>FREEZING/MELTING POINT (deg. C):</b>  | Not established              |
| <b>BOILING POINT (deg. C):</b>           | Not established              |
| <b>FLASH POINT:</b>                      | 27C; 81F TCC                 |
| <b>EVAPORATION RATE:</b>                 | Not established              |
| <b>FLAMMABILITY:</b>                     | Not a flammable solid or gas |
| <b>UPPER EXPLOSIVE LIMIT (% in air):</b> | Not established              |
| <b>LOWER EXPLOSIVE LIMIT (% in air):</b> | Not established              |
| <b>VAPOR PRESSURE (mm Hg):</b>           | Not established              |
| <b>VAPOR DENSITY:</b>                    | Not established              |
| <b>WEIGHT PER GALLON (lbs.):</b>         | 9.60                         |
| <b>SPECIFIC GRAVITY:</b>                 | 1.150                        |
| <b>SOLUBILITY:</b>                       | Not established              |

Print Date: 06-01-2015

FOSTER 90-66 PART B  
802432PM

---

**SAFETY DATA SHEET**


---

|  |                        |
|--|------------------------|
| OCTANOL/WATER COEFFICIENT:   | Not established        |
| AUTOIGNITION TEMPERATURE:  | Not established        |
| DECOMPOSITION TEMPERATURE:   | Not established        |
| VISCOSITY:   | No data available.     |
| SOLIDS (% by weight):  | 75.0                   |
| VOC, weight percent  | 24.90                  |
| VOC, U.S. EPA Method 24, less water and exempt solvents (theoretically determined) | 286g/liter of material |

---

**SECTION 10: STABILITY AND REACTIVITY**


---

STABILITY: Stable under normal conditions.  
 CONDITIONS TO AVOID: Oxidizing conditions. Contamination

CHEMICAL INCOMPATIBILITY: Not established  
 HAZARDOUS POLYMERIZATION: Will not occur.  
 HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide Manganese dioxide

---

**SECTION 11: TOXICOLOGICAL INFORMATION**


---

**Component Toxicity / Toxicology Data:**

| COMPONENT NAME                | LD50/LC50   |
|-------------------------------|---|
| Aromatic petroleum distillate | INHALATION LC50-4H RAT 3,400.00 PPM<br>DERMAL LD50 RABBIT > 2,000.00 MG/KG                            |
| Toluene                       | ORAL LD50 RAT 636 MG/KG<br>INHALATION LC50-4H RAT 12.50 MG/L<br>DERMAL LD50 RABBIT 8,390.00 MG/KG     |
| Manganese compounds           | ORAL LD50 RAT 9,000 MG/KG   |
| Trimethylbenzene, 1,2,4-      | ORAL LD50 RAT 3,400 MG/KG<br>INHALATION LC50-4H RAT 18.00 G/M3<br>DERMAL LD50 RABBIT > 3,160.00 MG/KG |
| Hydrogenated terphenyls       | ORAL LD50 RAT 10,200 MG/KG<br>INHALATION LC50-4H RAT > 4.30 MG/L<br>DERMAL LD50 RABBIT 6,800.00 MG/KG |
| Terphenyls                    | ORAL LD50 MOUSE > 50,000 MG/KG<br>DERMAL LD50 RABBIT > 12,500.00 MG/KG                                |

**This product is a mixture. Unless noted, the information below is based on components.**

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation :Eye contact may cause moderate to severe eye irritation. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: Contains a substance that is a probable reproductive hazard based on human studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause drowsiness or dizziness. May cause respiratory irritation.

Specific target organ toxicity-repeated exposure: No data available.

Print Date: 06-01-2015

FOSTER 90-66 PART B  
802432PM

---

**SAFETY DATA SHEET**


---

Target organs potentially affected by exposure: Lungs Reproductive system Liver Central nervous system Blood Kidneys Hemato System

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Lung disease, Liver disease, Blood disorders (like anemia), Kidney disease

---

**SECTION 12: ECOLOGICAL INFORMATION**


---

OVERVIEW: No ecological information available for this product.  
 MOBILITY: No data available.  
 PERSISTENCE: No data available.  
 BIOACCUMULATION: No data available.

**This product has not been tested for ecological effects. Relevant information for components is listed below:**

| <b>Component:</b>             | <b>Ecotoxicity values:</b>   |
|-------------------------------|--|
| Aromatic petroleum distillate | <b>Acute Toxicity (Fish):</b> 96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L<br><b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: 6.14 mg/L<br><b>Acute Toxicity (Algae):</b> Not established  |
| Toluene                       | <b>Acute Toxicity (Fish):</b> 96 Hr LC50 Pimephales promelas: 15.22 - 19.05 mg/L [flow-through] (1 day old); 96 Hr LC50 Pimephales promelas: 12.6 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.89 - 7.81 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 14.1 - 17.16 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.8 mg/L [semi-static]; 96 Hr LC50 Lepomis macrochirus: 11.0 - 15.0 mg/L [static]; 96 Hr LC50 Oryzias latipes: 54 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 28.2 mg/L [semi-static]; 96 Hr LC50 Poecilia reticulata: 50.87 - 70.34 mg/L [static]<br><b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: 5.46 - 9.83 mg/L [Static]; 48 Hr EC50 Daphnia magna: 11.5 mg/L<br><b>Acute Toxicity (Algae):</b> 96 Hr EC50 Pseudokirchneriella subcapitata: >433 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 12.5 mg/L [static] |
| Trimethylbenzene, 1,2,4-      | <b>Acute Toxicity (Fish):</b> 96 Hr LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through]<br><b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: 6.14 mg/L<br><b>Acute Toxicity (Algae):</b> Not established  |
| Hydrogenated terphenyls       | <b>Acute Toxicity (Fish):</b> 96 Hr LC50 Pimephales promelas: >0.53 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.53 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: >0.53 mg/L [static]<br><b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: 0.011 mg/L<br><b>Acute Toxicity (Algae):</b> 96 Hr EC50 Pseudokirchneriella subcapitata: >0.53 mg/L  |
| Terphenyls                    | <b>Acute Toxicity (Fish):</b> 96 Hr LC50 Oncorhynchus mykiss: >0.11 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.11 mg/L [static]; 96 Hr LC50 Pimephales promelas: >0.11 mg/L [static]<br><b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: >0.11 mg/L<br><b>Acute Toxicity (Algae):</b> 96 Hr EC50 Pseudokirchneriella subcapitata: 0.02 mg/L   |

---

**SECTION 13: DISPOSAL CONSIDERATIONS**


---

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Toluene Xylenes (o-, m-, p- isomers)

---

**SECTION 14: TRANSPORT INFORMATION**


---

Consult Bill of Lading for transportation information.

Print Date: 06-01-2015

FOSTER 90-66 PART B  
802432PM**SAFETY DATA SHEET**

US DOT: UN1139, COATING SOLUTION, 3, III, MARINE POLLUTANT (TERPHENYLS)  
IATA: UN1139, COATING SOLUTION, 3, III, MARINE POLLUTANT (TERPHENYLS)  
IMDG: UN1139, COATING SOLUTION, 3, III, MARINE POLLUTANT (TERPHENYLS), FLASH POINT 27°C C.C., EMS F-E, S-E

**SECTION 15: REGULATORY INFORMATION****INVENTORY STATUS**

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.  
CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from DSL requirements.  
EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.  
AUSTRALIA AICS: This product is in compliance with the Australian Inventory of Chemical Substances requirements.  
KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List requirements.  
PHILIPPINES: This product is in compliance with the Philippine Inventory of Chemicals and Chemical Substances requirements.  
CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at [reg.request@hbfuller.com](mailto:reg.request@hbfuller.com) to request an export review.

**FEDERAL REPORTING****EPA SARA Title III Section 313**

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

| Chemical Name          | CAS#      | %       |
|------------------------|-----------|---------|
| Toluene                | 108-88-3  | 5 - 10  |
| Manganese compounds    | 1313-13-9 | 5 - 10  |
| 1,2,4-Trimethylbenzene | 95-63-6   | 5 - 10  |
| Xylene (mixed isomers) | 1330-20-7 | 0.1 - 1 |
| Cumene                 | 98-82-8   | 0.1 - 1 |

**STATE REPORTING****Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:**

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

| Chemical Name/List                           | CAS       | Percent |
|--|-----------|---------|
| Carbon black (Carcinogen)                    | 1333-86-4 | 30 - 50 |
| Cumene (Carcinogen)                          | 98-82-8   | 0.1 - 1 |
| Toluene (Developmental toxin)                | 108-88-3  | 5 - 10  |
| Benzene, methyl- (Female reproductive toxin) | 108-88-3  | 5 - 10  |

Print Date: 06-01-2015

FOSTER 90-66 PART B  
802432PM**SAFETY DATA SHEET**

---

**Substances of Very High Concern (SVHC) Content:**

Unless listed below, this product does not contain SVHC's.

**SECTION 16: OTHER INFORMATION**

---

---

SDS VERSION DATE: 05-21-2015

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 3 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.



## **ANNEX A – TO HB FULLER: FOSTER 90-66B SEALER/COATING SDS DATED 21 MAY 2015**

### **CONTACT POINT**

For further information on this product please contact:

Australasian Insulation Supplies Pty Ltd  
(ABN 25 612 643 993)  
56 Cutler Road  
Jandakot WA 6164  
Telephone: (08) 9417 9494  
Facsimile: (08) 9417 9595  
Email: [sales@ais-group.com.au](mailto:sales@ais-group.com.au)

**EMERGENCY PHONE NO.** 000 Fire brigade and Police (Australia)

**POISONS INFORMATION** 13 11 26 (Australia)

HB Fuller Emergency No. (Australia) 1800 033 111

### **IMPORTANT NOTICE**

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information.